

# Boshart Pipe Fittings & Accessories

## Push Fit

Contact us to Order and/or  
for Pricing!  
[info@purewatersupplies.net](mailto:info@purewatersupplies.net)

### **Ball Valve, Brass, Full Port No Lead**

An excellent choice for a variety of applications where there is low risk of corrosion. Maximum pressure rating 200 psi. Available in 1/2"; 3/4"; 1"

CERTIFICATIONS: ASSE 1061-2006; No Lead; NSF / ANSI 372



### **Ball Valve with Drain, Brass, Full Port No Lead**

Perfect for applications where water needs to be drained from the pipe after the valve. When installing, make sure the drain is NOT installed on the supply side of the valve. Maximum pressure rating 200 psi.

Available in 1/2"; 3/4"; 1"

CERTIFICATIONS: ASSE 1061-2006; No Lead; NSF / ANSI 372



### **For the Brass Items that Follow**

All are approved for use for both underground and behind walls, with or without access panels. Excellent for repairs of existing plumbing where a system is hard to drain making soldering difficult. Connect copper, CPVC and PEX pipe in any combinations. Fittings can be rotated after assembly for easier installation in tight spaces and do not require tools, soldering flux, clamps, unions or glue.

For tube sizes 3/8" (0.5" O.D.), 3/4" (0.875" O.D.), 1" (1.125" O.D.)

### **CTS Coupling**

Available in 1/2"; 3/4" x 1/2"; 3/4"; 1" x 3/4"; 1" - Other sizes available upon request

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



### **CTS Transition Coupling**

Available in 1/2"; 3/4"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



# Boshart Pipe Fittings & Accessories

## Push Fit

Contact us to Order and/or  
for Pricing!  
[info@purewatersupplies.net](mailto:info@purewatersupplies.net)

### CTS Cap

Available in 1/2"; 3/4"; 1"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



### CTS x FPT Drop Ear 90° Elbow

Available in 1/2"; 3/4" x 1/2"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



### CTS 90° Elbow

Available in 3/8"; 1/2"; 3/4" x 1/2"; 3/4"; 1"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



### CTS x FPT 90° Elbow

Available in 1/2"; 3/4"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



### CTS x MPT 90° Elbow

Available in 1/2"; 3/4"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



# Boshart Pipe Fittings & Accessories

## Push Fit

Contact us to Order and/or  
for Pricing!  
[info@purewatersupplies.net](mailto:info@purewatersupplies.net)

### CTS Tee

Available in 3/8"; 1/2"; 3/4" x 1/2" x 1/2"; 3/4" x 1/2" x 3/4"; 3/4" x 3/4" x 1/2"; 3/4"; 1" x 1" x 3/4"; 1"  
CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



### CTS x FPT Adapter

Available in 3/8"; 1/2" x 3/4"; 1/2"; 3/4"; 1"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



### CTS x MPT Adapter

Available in 3/8"; 1/2" x 3/4"; 1/2"; 3/4"; 1"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



### CTS Repair Coupling

Available in 1/2"; 3/4"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



### CTS Tube Support

Available in 1/2"; 3/4"; 1"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



# Boshart Pipe Fittings & Accessories

## Push Fit

Contact us to Order and/or  
for Pricing!  
[info@purewatersupplies.net](mailto:info@purewatersupplies.net)

### CTS Disconnect Tool

Available in 1/2"; 3/4"; 1"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 61



### CTS Flexible Repair Coupling

Available in 1/2"; 3/4"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 372; NSF / ANSI 61



### CTS x FPT Water Connector

Available in 1/2"; 1/2" x 3/4"; 3/4"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 372; NSF / ANSI 61



### CTS x FPT Water Connector with Valve

Available in 1/2" x 3/4"; 3/4"

CERTIFICATIONS: ASSE 1061-2006; cUPC Certified; No Lead; NSF / ANSI 372; NSF / ANSI 372; NSF / ANSI 61

