# Boshart Pipe Fittings & Accessories Reducing Couplings

#### Reducing Coupling—Class 150 Heavy 316 Stainless Steel Fittings

3/4" x 1/2"; 1" x 3/4"; 1 1/4" x 1" - Other sizes available upon request CERTIFICATIONS: ANSI / ASME B1.20.1; ASTM A351; MSS SP114; No Lead; NSF / ANSI 372



#### Reducing Coupling—Class 150 Heavy 304 Stainless Steel Fittings

3/4" x 1/2"; 1" x 3/4"; 1 1/4" x 1" - Other sizes available upon request CERTIFICATIONS: ANSI / ASME B1.20.1; ASTM A351; MSS SP114; No Lead; NSF / ANSI 372



## Reducing Coupling—Class 150 Light 304 Stainless Steel Fittings

3/4" x 1/2"; 1" x 3/4"; 1 1/4" x 1" - Other sizes available upon request CERTIFICATIONS: ANSI / ASME B1.20.1; ASTM A351; ISO 4144; No Lead; NSF / ANSI 372



## Reducing Coupling—Class 150 Light 316 Stainless Steel Fittings

3/4" x 1/2"; 1" x 3/4"; 1 1/4" x 1" - Other sizes available upon request CERTIFICATIONS: ANSI / ASME B1.20.1; ASTM A351; ISO 4144; No Lead; NSF / ANSI 372



# Reducing Coupling—Female Flare x Male Flare

1/4" x 3/8"; 3/8" x 1/4"; 1/2" x 3/8"; 1/2" x 5/8"

Flare fittings are suitable for use in the plumbing and heating industries for gas, oil, air and water. They are applicable with aluminum, brass, copper and steel tubing. Flare fittings can be disassembled and resassembled many times with no effect on the seal.

